Schedule of Quantity

Issue to:-Date :-Name of Work :- Purchase of Street Light Drivers AND Relay Contactors for Timers etc. for MC Mandi H.P. Sr. No. Item No. Rate in figure Rate in Word Qtv. Units **Amount** TS2M1 series Timer (Supply voltage 230 V AC, Relay rating 16 A @ 250 V AC of ISI 8.00 No. 1 or BIS specifications. Relay Contactors (for street light timer panel) (Coil Voltage :230V AC-Contact Raing: Minimum 95-110 A, 3-Pole-Suitable for automatic street light switching-12.00 No. Make:L&T / Siemens/ Schneider / ABB or equivalent-Heavy duty, dustproof, with auxilary contacts of ISI or BIS 2 specifications LED Street light Driver - 20W (140-270 Volt universal electronic driver with internal surge protection of > 3kv. Wide range of 40.00 No. voltage to withstand the fluctuation of ISI 3 or BIS specifications) LED Street Light Driver-35 W (140-270 Volt universal electronic driver with internal surge protection of > 3kv. Wide range of 40.00 No. voltage to withstand the fluctuation of ISI 4 or BIS specifications) LED Street Light Driver-70 W (140-270 Volt universal electronic driver with internal surge protection of > 3kv. Wide range of 40.00 No. voltage to withstand the fluctuation of ISI 5 or BIS specifications)

> Assistant Engineer Municipal Corporation Mandi (H.P.)

LED Street Light Driver-130 W (140-270 Volt universal electronic driver with internal surge protection of > 3kv. Wide range of voltage to withstand the fluctuation of ISI or BIS specifications)	40.00	No.		* **
TOTAL				

Assistant Ingineer Municipal Corporation Mandi (H.P.)